

100 | DIRECT HEATED BOILING PAN

GENERAL DESCRIPTION

Chassis:
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- **Top:**
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.

- **Legs:**
200 mm high AISI 304 stainless steel legs, diam.: 60 mml. Adjustable PVC feet (0 / + 30).

Natural gas flow
G20/20 :

-

Propane gas flow
G31/37 :

-

REFERENCE : E1MF100CD



APPLIANCE DESCRIPTION

Dimensions (mm) : W : 850 x D : 800 x H 900.

- Features :

- . 100 liter tank, 2 mm thick AISI 316 stainless steel bottom and 2 mm side AISI304 stainless steel sides (internal dimensions : W : 540 x D : 500 x H 400)
- . Cove vertical and horizontal edges
- . Inclined bottom,
- . Removable stainless steel strainer, front drain tap with foldable handle.
- . AISI 304 stainless steel lid with tubular insulated handle on stainless steel spring hinges.
- . Direct heated by armoured heating element under the tank.
- . Control by simmerstat 0-100% with 'OFF' position.
- . "ON/OFF" Indicator light








- Electrical rating : 10.8 kW / 3~400V+E.

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
V01695	850 X 800 X 900	3~400V+E	ELEC : 10.8 kW	115 kg

OPTIONS	CODE
AISI 316 L stainless steel tank	V01433
Equipment for a 24V remote control	V00878
Terminal block for energy saver device	V02427
Overheat safety cut-out device	V01323
Counter balanced lid	V00569
Stainless steel rear panel fitted in factory	V01182
Stainless steel plinth to clamp on legs	V01187
-	-
-	-
-	-

ACCESSORIES	CODE
Mixer HW/CW water tap 20x27 (360°)	V00561
Mixer HW/CW water tap 20x27 (180°)	V01651
Hole cut to suit client's tap	V01292



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t-h...°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf desagüe</p>
			<p>3~400V + PE P: 10,8 kW Ø 15x21 (1/2") Ø 15x21 (1/2") Ø 100 mm</p>			
	<p>V01695 PRO800E1MF100CD</p>					