

GENERAL DESCRIPTION

Chassis:
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- **Top:**
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.

- **Legs:**
200 mm high AISI 304 stainless steel legs, diam.: 60 mml. Adjustable PVC feet (0 / + 30).



APPLIANCE DESCRIPTION

Dimensions (mm) : W : 850 x D : 800 x H : 900.

- **Top :**
. Neutral worktop

- **Base :**
. Cupboard with 2-piece floor in stainless steel
. Hinged doors and inner doors in stainless steel with magnetic hasps and handle
. One shelf

Natural gas flow
G20/20 :

-

Propane gas flow
G31/37 :

-


















REFERENCE : B-ETAG/P

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
V01712	850 X 800 X 900	-	-	60 kg

OPTIONS	CODE
150 mm wide plating shelf	V00806
Stainless steel rear panel fitted in factory	V01182
Stainless steel plinth to clamp on legs	V01187
Panel + enamelled front panel (5 level remaining in the cabinet)	S00027
-	-
-	-
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
-	-
-	-
-	-



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf de-sage</p>
 						
  						
     <p>V01712 PRO 800 PLACARD</p>						