

### GENERAL DESCRIPTION

Chassis:  
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- Top:  
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.



### APPLIANCE DESCRIPTION

Dimensions (mm) : W : 850 x D : 800 x H : 320/380.

- Top :  
. Neutral worktop with enamel front panel

- Base :  
. Bridge unit

Natural gas flow  
G20/20 :

-

Propane gas flow  
G31/37 :













-

REFERENCE : R-CAISSON

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
<b>V01717</b>	850 X 800 X 320/380	-	-	35 kg

OPTIONS	CODE
150 mm wide plating shelf	V00806
-	-
-	-
Stainless steel rear panel fitted in factory	V01290
-	-
-	-
-	-
-	-
-	-
-	-
-	-
ACCESSORIES	CODE
-	-
-	-
-	-



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf de-sague</p>
 						
 						
 <p><b>V01717 Pro 800 R-CAISSON</b></p>						

