



HALF MODULE UNIT - 2 OPEN BURNERS

BRIDGE UNIT

Pro 900

Summary

Energy :

GAS

Code :

V01735

Designation :

R-G2FN

Dimensions (W x D x H) :
425 x 900 x 320/380 mm
Power : 16,5 kW (gas)
Voltage/Electric p. :
Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Above :

- . 2 open burners under cast iron grids of: 420 x 300 mm.
- . Crown type "I.SYSTEM" burners, power: 10 kW at the front and 6.5 kW at the rear, with pilot lights and thermocouple safety.
- . "Stop - ignition - full fire - idle" valves with backlash adjustment
- . Removable enamelled steel toilet bowl
- . 1 stainless steel wire grid reducer
- . Cleanliness drawer in 18-10 stainless steel
- . Chassis (only if several stoves):
- . Assembly frame in 18-10 stainless steel tube 30 x 60 x 1 mm and profiles in 18-10 stainless steel sheet 30/10 thick, with plates for fixing the stoves



Natural gas flow G20/20 :

1,74

Propane gas flow G31/37 :

1,28

OPTIONS

















CODE

Removable water tank 1-230V+E /0,008 Kw	V02233
Electric spark ignition 1-230V+E/0,002 kW	V01013
"Double-crown" burner 8 kW in place of 1 standard burner	V02459
" IS ECO " burner in place of 2 standard burners 1-230V + E	V02890
S/S rear panel fitted in factory W : 415/490 x H : 645 mm	V01290

ACCESSORIES

CODE



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Auilanträge Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf Wasserzulauf (gef. filtertes wasser) ≤ 3 bars-7°F Conexión agua ≤ 3 bars-4.7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>
				     <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm² Ø 8x13 (1/4") Ø 20x27 (F3/4")</p>	<p>v01735 PRO900-1/2R-G2FN</p>	



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

