



HALF MODULE UNIT - SMALL SOLID TOP

BRIDGE UNIT

Pro 900

Summary

Energy :

GAS

Code :

V01736

Designation :

R-G1PL

Dimensions (W x D x H) :

425 x 900 x 320/380 mm

Power : 7 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Above :

1 hotplates:

- . Cast iron plate of: 420 x 600 mm with off-center plug
- . Crown type burner, power: 7 kW with pilot burner and thermocouple safety device
- . "Stop - ignition - full fire - idle" valve with backlash adjustment
- . Removable refractory elements in stainless steel formwork
- . Cleanliness drawer in 18-10 stainless steel
- . Chassis (only if several stoves):
- . Assembly frame in 18-10 stainless steel tube 30 x 60 x 1 mm and profiles in 18-10 stainless steel sheet 30/10 thick, with plates for fixing the stoves



Natural gas flow G20/20 :

0,74

Propane gas flow G31/37 :

0,54

OPTIONS

CODE

Electric spark ignition 1-230V+E/0,002 Kw

V00567


















S/S rear panel fitted in factory W : 415/490 x H : 645 mm

V01290

ACCESSORIES

CODE



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Ablaufgerätee Ablaufgerätee Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf Wasserzulauf (gef. filtertes wasser) ≤ 3 bars-7°F Conexión agua Conexión agua ≤ 3 bars-7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>
						
						
		     <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm²</p>		<p>v01736 PRO900-1/2R-GIPL</p>		



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

