



HALF MODULE UNIT - 2 OPEN BURNERS

OPEN BASE - 1 FLOOR

Pro 900

Summary

Energy :

GAS

Code :

V01952

Designation :

B-G2FN

Dimensions (W x D x H) :

425 x 900 x 900 mm

Power : 16,5 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electric welds and lower rear release for passage of cables and supply tubes.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Base :

Feet, height 200 mm, in AISI 304 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



Top :

. 1 set of 2 open burners under cast iron pan support measuring 420 x 300 mm

. "crown" burner rated 10 kW (front) and 6.5 kW (back), with flame failure safety cut out thermocouple - Pilot ignition

. recessed low and high heat controls

. Enamelled removable spillage tray

. Lower 18-10 stainless steel spillage drawer

Base :

. Open base with a 18-10 stainless steel removable 1-piece floor

Natural gas flow G20/20 :

1,74

Propane gas flow G31/37 :

1,28

OPTIONS

CODE














Elec hot cupboard 4xGN2/1 in base 1~230V+E / 1,50 kW - therm. 0-30/110°C	V00825
Hinged door for open base	V01980
Removable water tank 1-230V+E /0,008 kW	V02233
Electric spark ignition 1-230V+E/0,002 kW	V01013
"Double-crown" burner 8 kW in place of 1 standard burner	V02459
" IS ECO " burner in place of 2 standard burners 1-230V + E	V02890
12:00:00 AM	

ACCESSORIES

CODE

S/S clip on plinth panels H : 170 mm for standard legs	V01186



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Ausrüstung Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf Wasserzulauf (gef. filtertes wasser) ≤ 3bars-7°F Conexión agua Conexión agua ≤ 3 bars-4.7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>
					 	 <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm² Ø 8x13 (1/4") Ø 20x27 (F3/4")</p> <p>v01952 PRO900-1/2B-G2FN</p>



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr



YouTube

