



## BOILING PANS - BOILING PANS DIRECT HEATING 100 L.

### RECTANGULAR TANK

# Pro 900

## Summary

**Energy :**

**ELEC**

**Code :**

**V02063**

**Designation :**

**E1MF100CD**

**Dimensions (W x D x H) :**

**850 x 900 x 900 mm**

**Power : 10,8 kW (elec)**

**Voltage/Electric p. : 3~400V+N+E / 10,8**

**Weight :**

## DEVICE DESCRIPTION

### General description

**Chassis :**

**One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds and lower rear step for passage of cables and supply tubes.**

**Top :**

**Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.**

**Base :**

**Feet, height 200 mm, in 18-10 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).**

**Natural gas flow G20/20 :**

**Propane gas flow G31/37 :**

**Cooking pot :**

- . Rectangular tank capacity 100 liters:
- . Boiled tank in 20/10 stainless steel, bottom of tank in 316L stainless steel and ferrule in 18-10 stainless steel, with rounded vertical and horizontal angles, sloping bottom
- . Removable strainer in 18-10 stainless steel
- . Chrome-plated bronze drain valve on the front with folding handle
- . Internal dimensions (mm): W: 540 x D: 500 x H: 400
- . Cover in 18-10 stainless steel 15/10 thick with stainless steel spring hinge (s) for keeping "open", and operating lever in stainless steel tube with insulating handle

**Heating :**

- . Resistance frame, power 10.8 kW, voltage 3 ~ 400V + N + T
- . Control by energy metering device (0 - 100%) with stop position - indicator light



### OPTIONS

### CODE

AISI 316L tank for saline and/or acid foods	V01433
Equipment for a 24V remote control contactor(s) not supplied	V00878
Terminal block for energy saver device to regulate energy	V02427
Counter balanced lid in all positions	V00569
S/S rear panel fitted in factory W : 415/840 x H : 645 mm	V01182
Mixer water tap CW/HW Ø 15x21 swivel spout 360°	V00561
Mixer water tap CW/HW Ø 15x21 swivel spout 180°	V01651
Hole cut to suit client's tap - tap supplied and fitted by client	V01292

### ACCESSORIES

### CODE

S/S plinth to clamp on legs H : 170 mm for standard legs	V01187



