

CHARGRILL

OPEN BASE

GENERAL DESCRIPTION

Chassis:
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- **Top:**
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.

- **Legs:**
200 mm high AISI 304 stainless steel legs, diam.: 60 mml. Adjustable PVC feet (0 / + 30).

Natural gas flow G20/20 :	1,06 l/h
------------------------------	----------

Propane gas flow G31/37 :	0,78 kg/h
------------------------------	-----------

REFERENCE : 1/2 B-G1GRILPIER-V



APPLIANCE DESCRIPTION

Dimensions (mm): W : 425 x D : 800 x H : 900.

- Top :
 - . Chargrill with refractory briquets.
 - . 1 stainless steel "V-shaped" griddle measuring 365x485 mm each with handle and 3 positions adjustment.
 - . Grease collection bucket in the cupboard
 - . 'Multi-ramps' stainless steel burner located in a stainless steel fire box.
 - . Stainless steel support grid for briquets.
 - Control : flame failure safety cut-out thermocouple; recessed gas tap (OFF/Full power/slow-down positions).
 - . AISI 304 stainless drip tray in front.
 - Base :
 - . Open base
- Gas rating : 10 kW.

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
V02078	425 X 800 X 900	-	GAS : 10 kW	75 kg

OPTIONS	CODE
150 mm wide plating shelf	V00805
Hinged door for open base	V01937
Electric ignition for burners (Requires 1~230V+E supply)	V00567
Stainless steel rear panel fitted in factory	V01181
Stainless steel plinth to clamp on legs	V01186
-	-
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
Set of refractory briquets	V02250
-	-
-	-



				<p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>
				<p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>
				<p>Options Options Aufanfrage Opciones</p>
				<p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>
				<p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>
				<p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>
				<p>Ecoulement eaux usées sewage outflow wasserablauf de-sague</p>
			<p>Ø 15x21 (1/2") P: 10 kW 1~230V + PE P: 0,002 kW</p>	
			<p>V02078 PRO800-1/2B-G1GRILPIER-V</p>	

