



**FULL MODULE UNIT - 2 CAST-IRON CHARGRILLS OVER 1 TANK**

**OPEN BASE**

**Pro 900**

**Summary**

**Energy :**

**GAS**

**Code :**

**V02082**

**Designation :**

**B-G2GRILPIER-1B**

**Dimensions (W x D x H) :**

**850 x 900 x 900 mm**

**Power : 30 kW (gas)**

**Voltage/Electric p. :**

**Weight :**

## DEVICE DESCRIPTION

### General description

**Chassis :**

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electric welds and lower rear release for passage of cables and supply tubes.

**Top :**

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

**Base :**

Feet, height 200 mm, in AISI 304 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



. 1 stainless steel fireplace with plume

Above :

. 2 refractory bricks grills:

. 400 x 470 cooking grid in openwork cast iron, with handles and height adjustment device on 3 levels

. Stainless steel support grid for refractory bricks (12 mm diameter rounds)

. Multi - ramp burner in stainless steel tube, power 13 kW with pilot burner and thermocouple safety device

. "Stop - full fire - slow motion" valve with play compensation

. Cleanliness drawer in 18-10 stainless steel

Below:

. Free bay with removable 18-10 stainless steel floor in 2 parts

**Natural gas flow G20/20 :**

2,75

**Propane gas flow G31/37 :**

2,02

### OPTIONS

### CODE

Hinged doors for open base

V01576

Electric spark ignition 1-230V+E/0,002 kW

V01013

S/S rear panel fitted in factory W : 840 x H: 645 mm

V01182

### ACCESSORIES

### CODE

Removable splash guard for 1 griddle

V01562


















Recharge "refractory briquettes" set of 97 briquettes for 2 grills

V02253

S/S clip on plinth panels H : 170 mm for standard legs

V01187



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Ausrüstung Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Weichwasseranschluss Conexión agua suavizada ≤ 3bars-7°F Wasserzulauf (get. filtertes wasser) ≤ 3bars-7°F (GH) Conexión agua suavizada ≤ 3 bars-4.7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserablauf desagüe</p>	
						     <p>Ø 15x21 (1/2") 1~230V + PE Ø1.50mm²</p>	
							<p>V02082 PRO900B-C2GRILPIER-O-1B</p>



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)



YouTube

