

GENERAL DESCRIPTION

Chassis:
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- Top:
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.



APPLIANCE DESCRIPTION

Dimensions (mm) : W : 425 x D : 800 x H : 320/380.

- Top :
. AISI 304 stainless steel neutral work top with "Slide confort system" pull out utensil drawer under for an excluded GN1/1 container.

- Base :
. Bridge unit

Natural gas flow
G20/20 :

-

Propane gas flow
G31/37 :

-


















REFERENCE : 1/2 R-TIROIR1/1

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
V02222	425 X 800 X 320/380	-	-	40 kg

OPTIONS	CODE
150 mm wide plating shelf	V00805
-	-
-	-
Stainless steel rear panel fitted in factory	V01289
-	-
-	-
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
-	-
-	-
-	-



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf de-sage</p>
 						
  						
    						

V02222 PRO800-1/2R-TIROIR/I

