



HALF MODULE UNIT - CHARGRILL STAINLESS STEEL

BRIDGE UNIT

Pro 900

Summary

Energy :

GAS

Code :

V02271

Designation :

R-G1GRILPIER-V

Dimensions (W x D x H) :

425 x 900 x 320/380 mm

Power : 15 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity.

Top :


Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Above :

- . Refractory briquette grill
- . AISI304 stainless steel hearth with plume
- . Cooking grid 365 x 650 mm steel with handles and height adjustment device on 3 levels
- . Stainless steel bricks support grid (12 V-shaped bars)
- . AISI304 stainless steel juice collector in the upper part
- . Multi - ramp burner in anti - corrosion treated steel, P 13 kW with safety thermocouple
- . Slack adjustment "stop / full-ignition / idle" valve. Refractory briquettes for 1st charge
- . AISI304 stainless steel cleanliness drawer on the front

Below:

None -> to place or to hang



Natural gas flow G20/20 :

1,38

Propane gas flow G31/37 :

1,01

OPTIONS

CODE

Electric spark ignition 1-230V+E/0,002 Kw

V00567

S/S rear panel fitted in factory W : 415/490 x H : 265 mm

V01290

















ACCESSORIES

CODE

Recharge "refractory briquettes" set of 45 briquettes for 1 griddle

V02252



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Ausstattungen Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf (gef. filtertes wasser) ≤ 3 bars-7°F Conexión agua suavizada ≤ 3 bars-7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>
				     <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm²</p>	<p>v02271 PRO900-1/2R-GIRILLPIER-V</p>	



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

