

### GENERAL DESCRIPTION

Chassis:  
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- Top:  
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.



### APPLIANCE DESCRIPTION

Dimensions (mm) : W : 425 x D : 800 x H : 380

- Top :
  - . 16l capacity tank, 1 mm thick AISI 304 stainless steel, with cold and heat zones and a 20 mm high edge to prevent debris from falling in the cooking oil
  - . Oil level indicator marks
  - . Drain tap to front
  - . Hinged lid in AISI 304 stainless steel , 1 mm thick AISI 304 stainless steel
  - . Electric heating with removable immersed element rated 18 kW

- Control and safety :
- . On/Off switch, control thermostat and indicator lights
  - . Safety thermostat with manual reset
  - . Safety micro-switch to secure the position of the immersed element

- Accessory :
- . 1 large nickel coated fryer basket

- Base :
- . Bridge unit

Electrical rating : 18 kW / 3~400V+E

Output 40 kg/h blanched chips

Natural gas flow  
G20/20 :

-

Propane gas flow  
G31/37 :

-

















REFERENCE : 1/2 R-E1FR1618HR

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
<b>V02426</b>	425 X 800 X 380	3~400V+E	ELEC : 18 kW	40 kg

OPTIONS	CODE
150 mm wide plating shelf	V00805
-	-
-	-
Electronic regulation (230 V+E)	V01180
Equipment for a 24V remote control (1~230V+E)	V00878
Terminal block for energy saver device	V02427
Front electric socket (1~230V+E / 13 Amps)	V02248
2x1/2 fryer basket to replace 1 large basket	V02214
-	-
-	-

ACCESSORIES	CODE
Fryer basket	04062A
1/2 fryer baskets	07590A
Stainless steel fish plate	F02921



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf de-sage</p>
 						
 						
     <p>3~400V + PE P: 18 kW 1~230V + PE P: 0,192 kW</p> <p><b>V02426</b> PRO800-1/2R-E/FR1618HR</p>						