

NEUTRAL WORKTOP

FIXED FILTRATION UNIT

GENERAL DESCRIPTION

Chassis:
One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

- **Top:**
AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.

- **Legs:**
200 mm high AISI 304 stainless steel legs, diam.: 60 mml. Adjustable PVC feet (0 / + 30).

Natural gas flow
G20/20 :

-

Propane gas flow
G31/37 :

-

REFERENCE : 1/2 MODULFILTRE



APPLIANCE DESCRIPTION

















Dimensions (mm) : W : 425 x D : 800 x H : 900.

- Top :
 - . Neutral worktop
- Base :
 - . Removable integrated filtration bucket with pump on runners.
 - . Filtration through a micro perforated stainless steel grid.
 - . Up to 3 other fryers connectable with a selection by a system of ball taps
 - . Device for drainage to an excluded waste container.
 - . Light indicator.
 - . 70°C safety thermostat
 - . Hinged door and inner door in stainless steel with magnetic hasps and handle
- Electrical rating : 0.2 kW / 1~230+E

CODE	DIMENSIONS	ALIMENTATION	POWER	WEIGHT
V02617	425 X 800 X 900	1~230V+E	ELEC : 0.2 kW	50 kg

OPTIONS	CODE
150 mm wide plating shelf	V00805
Built in container	V01150
Overhead ceramic heater (2 kW / 2~400V+E)	V01215
Stainless steel rear panel fitted in factory	V01181
Stainless steel plinth to clamp on legs	V01186
-	-
-	-
-	-
-	-
-	-
ACCESSORIES	CODE
-	-
-	-
-	-



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanfrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-t.h...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°C/GH) Conexión agua blanda ≤ 3 bars-t.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf de-sague</p>
 						
 						
     <p>1 ~230V + PE</p> <p>V02617-VISU</p>						