



FULL MODULE UNIT - BURNER FOR PAËLLA

OPEN BASE

Pro 900

Summary

Energy :

GAS

Code :

V02791

Designation :

B-G1FP

Dimensions (W x D x H) :

850 x 900 x 900 mm

Power : 24 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electric welds and lower rear release for passage of cables and supply tubes.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Base :

Feet, height 200 mm, in AISI 304 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



Above :

. 1 set 600 * 600mm of 1 cast iron paella fire, removable brass head and steel / stainless steel (hexagonal) of 24 Kw.

. Safety by independent thermocouples on each burner with electric ignition.

. Steel or cast iron grids.

. Cleanliness drawer in 18-10 stainless steel.

. Gas connection: 1/2 " male thread or (larger diameter on the general supply rail depending on the composition of the assembly).

Below:

. Free bay with removable 18-10 stainless steel floor in 2 parts

Natural gas flow G20/20 :

2,54

Propane gas flow G31/37 :

1,86

OPTIONS

CODE

Elec hot cupboard 4xGN2/1 in base 3~400V+N+E / 2,25 kW - therm.

V00826

Hinged doors for open base

V01576

Electric spark ignition 1-230V+E/0,002 kW

Included

S/S rear panel fitted in factory W : 840 x H : 645 mm

V01182



















ACCESSORIES

CODE

S/S clip on plinth panels H : 170 mm for standard legs

V01187



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Ausstattung Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf Wasserzulauf (gef. filtertes wasser) ≤ 3 bars-7°F Conexión agua ≤ 3 bars-4 lb. 7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserlauf desagüe</p>	
							
				     <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm²</p>		<p>V02791 PRO900B-CIFP</p>	



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

