



HALF MODULE UNIT - GRIDDLE OVER WATER TANK

OPEN BASE

Pro 900

Summary

Energy :
ELEC

Code :
V02802

Designation :
B-E1GRBE/FTE

Dimensions (W x D x H) :
425 x 900 x 900 mm
Power : 6 kW (elec)
Voltage/Electric p. : 3~400V+N+E / 6
Weight :

DEVICE DESCRIPTION

General description

Chassis :

One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds and lower rear step for passage of cables and supply tubes.

Top :

Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.

Base :

Feet, height 200 mm, in 18-10 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).

Natural gas flow G20/20 :

Propane gas flow G31/37 :



Above :

- . Lift-up cast iron bar grill. Useful dimensions: 350 x 500 mm
- . Stainless steel resistors of section 5.5 x 13.5 mm
- . Regulation by energy regulator 0-100%, with off position
- . 'On' and 'regulation' LEDs
- . Power: 6kW, 3/400 + N + T Stamped stainless steel water tank with plug and drain valve in the base.














Basement:

- . Open bay with removable AISI 304 floor.

OPTIONS	CODE
Hinged doors for open base	V01980
Equipment for a 24V remote control contactor(s) not supplied	V00878
Drain tap to front included in bridge unit/compulsory if hot	V01818
S/S rear panel fitted in factory W : 415 x H : 645 mm	V01181

ACCESSORIES	CODE
S/S clip on plinth panels H : 170 mm for standard legs	V01186



 <p>Conexión gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Conexión eléctrica Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Aulage Options</p>	 <p>Conexión eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Conexión eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Conexión eau adoucie Softened water connection Weichwasseranschluss Conexión agua suavizada ≤ 3bars-7°F Wasserzulauf (gef. filtertes wasser) ≤ 3bars-7°F (GHD) Conexión agua suavizada ≤ 3 bars-4.7°F</p>	 <p>Ecolement eaux usées sewage outflow wasserlauf desagüe</p>
						 <p>3 ~ 400V + PE Ø1.50mm² Ø15x21 (1/2") M 26/34 (1")</p>
				<p>v02802 PRO900-1/2B-EI GRBE/FTE</p>		



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

