



# HALF MODULE UNIT - GRIDDLE OVER WATER TANK

## BRIDGE UNIT

# Pro 900

### Summary

<b>Energy :</b> ELEC	<b>Code :</b> V02803	<b>Designation :</b> R-E1GRBE/FTE
-------------------------	-------------------------	--------------------------------------

<b>Dimensions (W x D x H) :</b> 425 x 900 x 320/380 mm <b>Power : 6 kW (elec)</b> <b>Voltage/Electric p. : 3~400V+N+E / 6</b> <b>Weight :</b>
---

## DEVICE DESCRIPTION

### General description

**Chassis :**  
One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds.

**Top :**  
Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.




















- Above :
- . Lift-up cast iron bar grill. Useful dimensions: 350 x 500 mm
  - . Stainless steel resistors of section 5.5 x 13.5 mm
  - . Regulation by energy regulator 0-100%, with off position
  - . 'On' and 'regulation' LEDs
  - . Power: 6kW, 3/400 + N + T Stamped stainless steel water tank with plug and drain valve in the base.

<b>Natural gas flow G20/20 :</b>
<b>Propane gas flow G31/37 :</b>

OPTIONS	CODE
Equipment for a 24V remote control contactor(s) not supplied	V00878
Drain tap to front included in bridge unit/compulsory if hot	V01818
S/S rear panel fitted in factory W : 425 x H : 265 mm	V01290

ACCESSORIES	CODE



 <p>Connexion gaz Gas connection Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Aulänge Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf (gef. filtertes wasser) ≤ 3bars-7°F Conexión agua suavizada ≤ 3 bars-47°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>
					     <p>1 ~ 230V + PE Ø 1.50mm<sup>2</sup> Ø 15x21 (1/2") Ø 32x42 (M1" 1/4")</p>	<p>v02803 PRO000-1/2R-EI GRBE/FTE</p>



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)

