



HALF MODULE UNIT - PASTA COOKER

BRIDGE UNIT

Pro 900

Summary

Energy : ELEC	Code : V02926	Designation : R-E1CUIPAT1/1	Dimensions (W x D x H) : 425 x 900 x 320/380 mm Power : 11 kW (elec) Voltage/Electric p. : 3~400V+N+E / 11 Weight :
-------------------------	-------------------------	---------------------------------------	---

DEVICE DESCRIPTION

General description

Chassis :
One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity.

Top :
Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.




















- Above :
- . 1 stainless steel tank with double perforated bottom
 - . Internal dimensions of the tank: W 305 x D 520 H 230 mm
 - . Heating by removable immersion heater power 11 kW, controlled by an electronic thermostat
 - . Power indicator
 - . Starch washing device and sprinkler
 - . Drainage area for baskets with removable grids
 - . Drainage tube, plug for draining the tank
 - . Supply: 6 GN 1/6 baskets in stainless steel with insulating handle
 - . Optional automatic basket lifting

Natural gas flow G20/20 :
Propane gas flow G31/37 :

OPTIONS	CODE
S/S rear panel fitted in factory W : 425 x H : 265 mm	V01290
Automatic lift for baskets 1-230 V+E	V02929

ACCESSORIES	CODE



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Aulänge Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Softened water connector Wasserzulauf (gef. filtertes wasser ≤ bars abs. 7/8 F) Wasserzulauf (gef. filtertes wasser ≤ bars abs. 7/8 F) Wasserzulauf (gef. filtertes wasser ≤ 3 bars abs. 7/8 F)</p>	 <p>Evacuation eaux usées sewage outflow wässerschlauf desagüe</p>
					     <p>3~400V + N +PE P:11kW Ø15X21 (F-1/2") Ø40X49 (1-1/2")</p>	<p>V02926 1/2 PRO900 CUISFAT MOD10 RECHAUD</p>



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

