



FULL MODULE UNIT - STEEL PLATE 4 ZONES 3 x 4 KW

ELECTRIC OVEN GN 2/1

Pro 900

Summary

Energy :

ELEC

Code :

V03234

Designation :

E4PCF4ZONES

Dimensions (W x D x H) :

850 x 900 x 900 mm

Power : 17 kW (elec)

Voltage/Electric p. : 3~400V+N+E / 17

Weight : 170 kg

DEVICE DESCRIPTION

General description

Chassis :

One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds and lower rear step for passage of cables and supply tubes.

Top :

Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.

Base :

Feet, height 200 mm, in 18-10 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



Above :

- . 1 flush steel plate 700 x 500 mm (indirect cooking), 20 mm thick, mounted on a peripheral groove.
- . 4 armored electric fireplaces of 3 kW unit on refractory soil.
- . Individual regulation of the 4 hotplates by thermostats with off position and operating indicator lights.
- . Front cleanliness drawer (right side of the appliance)
- . GN2 / 1 static electric oven - W 530 x D 650 x H 300 mm.
- . Floor and roof heating by 3-400V + N + T resistors, P. 5 kW, controlled by an 8-position switch: "vault / 0 / sole / 0 / v + s soft / 0 / v + s high / 0 "and regulation thermostat 50-300 ° C. Indicator lights.
- . AISI304 stainless steel muffle, insulated, steel sole th. 4mm, removable enamelled steel dishes (3 levels spaced 70mm apart), GN2 / 1 grid in nickel-plated steel wire with anti-tilt (x1) + GN2 / 1 pastry plate (x1).
- . AISI304 stainless steel door and inner door, insulated, enamelled steel handle on aluminum supports.

Natural gas flow G20/20 :

Propane gas flow G31/37 :

OPTIONS

CODE

S/S rear panel fitted in factory W : 840 x H : 645 mm

V01182



















ACCESSORIES

CODE

S/S clip on plinth panels H : 170 mm for standard legs

V01187



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Ausstattung Aparatores Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connector Wasserzulauf ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ 3bars-7°F/311 Grad) Conexión agua ≤ 3 bars-4b. 7°F</p>	 <p>Ecoulement eaux usées sewage outflow wässerschlauf desagüe</p>	
							
				     <p>3~400V + Pe Ø2.00mm²</p>		<p>Ø 20x27 (F3/4")</p>	
				<p>V03234 PRO000E1PCF4ZONES</p>			



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

