



# FULL MODULE UNIT - STEEL PLATE 4 ZONES 3 x 4 kW

## OPEN BASE

# Pro 900

## Summary

<b>Energy :</b> ELEC	<b>Code :</b> V03235	<b>Designation :</b> B-E4PCF4ZONES
-------------------------	-------------------------	---------------------------------------

<b>Dimensions (W x D x H) :</b> 850 x 900 x 900 mm <b>Power : 12 kW (elec)</b> <b>Voltage/Electric p. : 3~400V+N+E / 12</b> <b>Weight : 155 kg</b>
--

## DEVICE DESCRIPTION

### General description

**Chassis :**  
One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds and lower rear step for passage of cables and supply tubes.

**Top :**  
Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.

**Base :**  
Feet, height 200 mm, in 18-10 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).

<b>Natural gas flow G20/20 :</b>
<b>Propane gas flow G31/37 :</b>



Above :













- . 1 flush steel plate 700 x 500 mm (indirect cooking), 20 mm thick, mounted on a peripheral groove.
- . 4 armored electric fireplaces of 3 kW unit on refractory soil.
- . Individual regulation of the 4 hotplates by thermostats with off position and operating indicator lights.
- . Cleanliness drawer on the front (right side of the appliance).

Base: Free-standing window with removable AISI 304 stainless steel floor in 2 parts.

OPTIONS	CODE
Elec hot cupboard 4xGN2/1 in base 3~400V+N+E / 2,25 kW - therm. 0-30/110°C	V00826
Hinged doors for open base	V01576
S/S rear panel fitted in factory W : 840 x H : 645 mm	V01182

ACCESSORIES	CODE
S/S clip on plinth panels H : 170 mm for standard legs	V01187



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Auilanlage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Soft water connection Weichwasseranschluss Conexión agua ablandada ≤ 3bars-7°F Wasserzulauf (gefaltetes wasser ≤ 3bars-7°F/3FD) Conexión agua ablandada ≤ 3 bars-ab. 7°F</p>	 <p>Ecoulement eaux usées sewage outflow Wasserablauf desagüe</p>
 						
						
  <p data-bbox="1125 985 1157 1198">3~400V + Pe Ø2.00mm²</p> <p data-bbox="1220 1064 1252 1220">Ø20x27 (3/4")</p> <p data-bbox="1228 1344 1252 1601"><b>V03235</b> PRO900 B-EI PCF4ZONES</p>						



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)

