



HALF MODULE UNIT - WOK TORCH

OPEN CUPBOARD

Pro 900

Summary

Energy :

GAS

Code :

V03495

Designation :

G1-WOK-TORCHE

Dimensions (W x D x H) :

500 x 900 x 900 mm

Power : 21 kW (gas)

Voltage/Electric p. : 1~230V+E

Weight :

DEVICE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electric welds and lower rear release for passage of cables and supply tubes.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

Base :

Feet, height 200 mm, in AISI 304 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



Above :

- . Cauldron size 30/10 with cold water supply by nozzle and fitted with a drain plug with filter basket in the lower part at the rear.
- . Water supply by solenoid valve.
- . Central nozzle diam. 300 mm x height 350 mm in AISI 304 stainless steel th. 30 to 60/10, torch burner with pilot light and safety thermocouple, controlled by a gas valve with backlash type " stop / ignition / full fire / idle " power: 21 kW.
- . Removable cast iron container support.
- . AISI 304 stainless steel cleanliness drawer on the front.
- . Refractory cement inside the cylindrical.
- . Knee control as standard.

Natural gas flow G20/20 :

Propane gas flow G31/37 :

OPTIONS

CODE

Electric spark ignition - 1-230V+E/0,002 kW

Included

S/S rear panel fitted in factory - W : 840 x H: 645 mm

V01181

ACCESSORIES

CODE

S/S clip on plinth panels - H : 170 mm for standard legs

V01186



<p>Connection gaz Gasanschluss Gasanschluss Conexión gas</p> <p>Connection électrique Electric connection Elektrische Verbindung Conexión eléctrica</p> <p>Options Optionen Auftritte Opciones</p> <p>Connection eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p> <p>Connection eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p> <p>Connection eau adoucie Softener Wasserzulauf (gefiltertes wasser ≤ bars-ab. 7(GH) Conexión agua blanda ≤ 9 bars-ch...7(F</p> <p>Ecoulement eaux usées sewage outflow wasserablauf desague</p>		
<p>Ø15/21 (1/2") 1~230V+PE Ø15/21 (1/2") Ø40/49 (1"~1/2)</p>	<p>V03495 1/2 PRO900 G1-WOK-TORCHE</p>	



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr



YouTube

