



HALF MODULE UNITS - CHROME PLANCHA

BRIDGE UNIT

Pro 800

Summary

Energy :

ELEC

Code :

V03506

Designation :

R-E1PL/CHR/RUIS

Dimensions (W x D x H) :

425 X 800 X 320/380 mm

Power : 5 kW (elec)

Voltage/Electric P. : 3~400V+N+E / 5 kW

Weight : 65 kg

APPLIANCE DESCRIPTION

General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electrical welds.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.



Top :

. 1 chromed XC48 steel plancha plate Dim. 690 x 490 mm, thickness 20 mm (chrome plating thickness 50µ), flush with the top, mounted on a boiler-lined peripheral groove.

. Heating by plated resistances - P.: 5 kW - control by limiting thermostat 100-350 ° C, signaling by indicator lights.

. Boiled peripheral groove with radiated angles and drain plug with removable overflow, water drainage (drainage connected to the ground to be provided).

. Emptying into tank (option).

. Sealing by penetrating the edge of the groove on the underside of the plancha.

Basement :

. None -> to be placed or suspended.

Natural gas flow G20/20 :

-

Propane gas flow G31/37 :

-

OPTIONS

CODE

150-mm wide plating shelf integrated into the top

V00805

Equipment for a 24V remote control contactor(s) not supplied

V00878

Draining in drawer for bridge unit only - Without water flushing

V03544

Stainless steel plancha to replace the chrome plancha

V03392

S/S rear panel fitted in factory - W : 425 x H : 265 mm

V01289

ACCESSORIES

CODE

Removable splash guard for 1 griddle or 1 plancha

V02682

-

-


















-

-

-

-



 <p>Connexion gaz Gas connection Gasanschluss Connexion gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Connexion eléctrica</p>	 <p>Options Options Auftrage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Connexion água fria</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Connexion água quente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°GH) Connexion água branda ≤ 3 bars-t.h., °F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf desague</p>
 						
  						
     <p>3~400V+N+PE Ø2.5mm² Ø15X21 (1/2") Ø40X49 (1"-1/2)</p> <p>V03506 PRO800-1/2-R-EL-PLANCHA-30/50-CHR RUISSELEAU</p>						



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr



YouTube

