



## FULL MODULE UNIT - STEEL PLANCHA

### OPEN BASE

# Pro 900

## Summary

**Energy :**

**ELEC**

**Code :**

**V03516**

**Designation :**

**B-E1PL/ACR/RUIS**

**Dimensions (W x D x H) :**

**850 x 900 x 900 mm**

**Power : 7,5 kW (elec)**

**Voltage/Electric p. : 3~400V+N+E / 7,5**

**Weight :**

## DEVICE DESCRIPTION

### General description

**Chassis :**

One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds and lower rear step for passage of cables and supply tubes.

**Top :**

Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.

**Base :**

Feet, height 200 mm, in 18-10 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).

**Natural gas flow G20/20 :**

**Propane gas flow G31/37 :**



**Above :**

- . 1 smooth plancha (contact cooking plate): steel plate of dimensions: 700 x 500 x 20 mm, flush.
- . Heating by plated resistances, power: 7,5 kW voltage: 3 ~ 400V + N + T
- . Control by energy metering device - indicator light.
- . Safety limiter thermostat.
- . Boiled peripheral groove with radiated angles and drain plug with removable overflow, water drainage (drainage connected to the ground to be provided). Emptying into tank (option).
- . Sealing by penetrating the edge of the groove on the underside of the plancha.

**Below:**

- . Free bay with removable floor in 2 parts.

### OPTIONS

### CODE



























Elec hot cupboard 4xGN2/1 in base 3~400V+N+E / 2,25 kW - therm. 0-30/110°C	V00826
Hinged doors for open base	V01576
Equipment for a 24V remote control contactor(s) not supplied	V00878
Draining in drawer for bridge unit only - Without water flushing	V03544
Drain pipe+tank in base for 2 chrome griddles or 1 plancha	V03545
4 heating zones on plancha power 12 Kw	V03491
S/S rear panel fitted in factory W : 840 x H : 645 mm	V01182

### ACCESSORIES

### CODE

S/S clip on plinth panels H : 170 mm for standard legs	V01187
Removable splash guard For 1 griddle or 1 plancha	V02597



 <p>Conexión gas Gas connection Gasanschluss Conexión gas</p>	 <p>Conexión eléctrica Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Opciones Options Aufanlage Opciones</p>	 <p>Conexión en frío Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Conexión en caliente Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Conexión en caliente Softened water connection ≤ 3bars-7°F Wasserlauf (gefiltertes wasser ≤ 3bars-7°F) Conexión agua ≤ 3 bars-7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserablauf desagüe</p>										
																
																
  <table border="1" data-bbox="1085 873 1248 1232"> <tr> <td></td> <td>3~400V+N+PE Ø2.5mm<sup>2</sup></td> </tr> <tr> <td></td> <td>Ø15X21 (1/2")</td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td>Ø40X49 (1"-1/2)</td> </tr> </table> <p data-bbox="1212 1276 1252 1612"><b>V03516</b> PRO000-B E1-PLANCHA-70-50 RUISSELEAU</p>								3~400V+N+PE Ø2.5mm <sup>2</sup>		Ø15X21 (1/2")						Ø40X49 (1"-1/2)
	3~400V+N+PE Ø2.5mm <sup>2</sup>															
	Ø15X21 (1/2")															
																
																
	Ø40X49 (1"-1/2)															



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)



YouTube

