



FULL MODULE UNIT - STEEL PLANCHA

BRIDGE UNIT

Pro 900

Summary

Energy :

ELEC

Code :

V03519

Designation :

R-E1PL/ACR/RUIS

Dimensions (W x D x H) :

850 x 900 x 320/380 mm

Power : 7,5 kW (elec)

Voltage/Electric p. : 3~400V+N+E / 7,5

Weight :

DEVICE DESCRIPTION

General description

Chassis :

One-piece seam welded 18-10 stainless steel chassis, 1,5 to 3 mm thick, assembled by high intensity electrical welds.

Top :

Top (frame) in 18-10 stainless steel, 30/10 thickness, with 55 mm front flanged edge and plywood.



Above :

- . 1 smooth steel plancha (contact cooking plate): plate dimensions: 700 x 500 x 20 mm, beyond
 - . Heating by plated resistors, power: 7.5 kW, voltage: 3 ~ 400V + N + T (power 12 kW with 4 zones option)
 - . Control by energy meter and indicator light
 - . Safety limiter thermostat
 - . Boiled peripheral groove with radiated angles and drain plug with removable overflow, water drainage (drainage connected to the ground to be provided). Emptying into tank (option).
 - . Sealing by penetrating the edge of the groove on the underside of the plancha.
- Chassis (only if several stoves):
- . Assembly frame in 18-10 stainless steel tube 30 x 60 x 1 mm and profiles in 18-10 stainless steel sheet 30/10 thick, with fixing plates for the stoves.

Natural gas flow G20/20 :

Propane gas flow G31/37 :

OPTIONS

CODE























Equipment for a 24V remote control contactor(s) not supplied	V00878
Draining in drawer for bridge unit only - Without water flushing	V03544
4 heating zones on plancha power 12 Kw	V03491
S/S rear panel fitted in factory W : 850 x H : 265 mm	V01290

ACCESSORIES

CODE

Removable splash guard For 1 griddle or 1 plancha	V02597



 <p>Conexión gas Gasanschluss Gasanschluss Conexión gas</p>	 <p>Conexión eléctrica Elektrik conexão Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Optionen Auftrags Optiones</p>	 <p>Conexión en frío Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Conexión en caliente Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Conexión en abollada Burr-t... Soft... Wasserlauf (gefällertes wasser ≤ Burr-ob... Conexión agua blanda ≤ Burr-t... F</p>	 <p>Ecolament aux usses sewage outflow wasserablauf desague</p>
						     <p>3~400V+N+PE Ø2.5mm² Ø15X21 (1/2") Ø40X49 (1" - 1/2)</p>
				    		<p>V03E10 PROP00-R EI-PLANCHA-7050 RUISSELEAU</p>



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

