



## FULL MODULE UNITS - STEEL PLANCHA 600 MM

### OPEN BASE

# Pro 800

## Summary

**Energy :**

**ELEC**

**Code :**

**V03570**

**Designation :**

**B-E1-PLANCHA-600**

**Dimensions (W x D x H) :**

**600 x 800 x 900 mm**

**Power : 5,25 kW (elec)**

**Voltage/Electric P. : 3~400V+N+E**

**Weight :**

## APPLIANCE DESCRIPTION

### General description

**Chassis :**

One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

Assembly by high intensity electric welding.

**Top :**

AISI 304 stainless steel top frame, 3 mm thick, with a 55 mm high edge and return to underside.

**Legs :**

200 mm high AISI 304 stainless steel legs, diam. : 60 mm. Adjustable PVC feet (0 / + 30).



**Above :**

. Plate 400 x 450 mm - steel - power : 5.25 kW.

. Controlled by thermostat 50-350 ° C.

. Power on indicator light.

. Boiled peripheral groove with radiated angles and drain plug with removable overflow, water drainage (Requires connection to mains drainage).

. Emptying into tank (option).

**Below :**

. Open base: 600 x 800 x 900 mm.

**Natural gas flow G20/20 :**

**Propane gas flow G31/37 :**

### OPTIONS

### CODE

150-mm wide plating shelf - integrated into the top

V03623

Electric hot cupboard 4xGN2/1 in base - 3-400V+N+E/2,25 kW-therm. 0-30/110°C

NA

Hinged doors - for open base

V03624

S/S rear panel fitted in factory - L: 840 x H: 645 mm

V03625

100% ribbed plate

V03629

1/2 smooth + 1/2 ribbed plate

V03628

### ACCESSORIES

### CODE


















S/S clip on plinth panels - H : 170 mm for standard legs

V03622

Removable splash guard - For 1 griddle

V03626



<p>              Conexión gas            Gas connection            Gasanschluss            Conexión gas         </p>	<p>              Conexión eléctrica            Electric connection            Elektrische Verbindung            Conexión eléctrica         </p>	<p>              Options            Optionen            Aufsträge            Opciones         </p>	<p>              Conexión en frío            Cold water connection            Kaltwasseranschluss            Conexión agua fría         </p>	<p>              Conexión en caliente            Hot water connection            Warmwasseranschluss            Conexión agua caliente         </p>	<p>              Conexión sin abrigue            Without hood connection            Ohne Abzug            Conexión sin abrigue            Softened water connection            ≈ 3bar-7°F            Wasserlauf (geföhertes            Wasser ≈ 3bar-7°F)            Conexión agua blanda            ≈ 3 bar-41,7°F         </p>	<p>              Ecoulement eaux usées            sewage outflow            Abwasserlauf            Abgabe         </p>
					 	<p>      </p> <p> <b>3-400V+N+T - 4mm<sup>2</sup></b>  <b>Ø15X21 (1/2")</b>  <b>Ø40X49 (1"-1/2)</b> </p> <p><b>V03570 PRO800-B-EI-PLANCHIA-600</b></p>



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)



YouTube

