



## BOILING PANS - BOILING PANS - WATER JACKETED

### CYLINDRICAL TANK

# Pro 800

## Summary

**Energy :**

**GAS**

**Code :**

**V03573**

**Designation :**

**G1MF100BMEC**

**Dimensions (W x D x H) :**

**850 x 800 x 900 mm**

**Power : 18 kW (gas)**

**Voltage/Electric P. : 1~230V+E**

**Weight :**

## APPLIANCE DESCRIPTION

### General description

**Chassis :**

One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

Assembly by high intensity electric welding.

**Top :**

AISI 304 stainless steel top frame, 3 mm thick, with a 55 mm high edge and return to underside.

**Legs :**

200 mm high AISI 304 stainless steel legs, diam. : 60 mm. Adjustable PVC feet (0 / + 30).



**Construction :**

. 100L round tank in AISI304 stainless steel, thick. 20/10 - diameter 500 x depth 530 mm, AISI316L stainless steel tank bottom, sloped bottom, removable stainless steel strainer, centered drain valve.

. AISI304 stainless steel cover th. 15/10 with spring-loaded hinge to keep it open and tube operating lever with insulating handle.

. AISI304 stainless steel double jacket, automatic filling (softened water recommended) safety unit (pressure gauge and valve 0.3bar).

. Heating by enamelled steel multi-ramp burner, with pilot burner and safety thermocouple, controlled by a gas thermostatic valve (combining the power supply, ignition, flame monitoring and regulation functions).

. Electric ignition by spark (manual ignition always possible).

. Power: 18 kW gas + 0.01 kW in 1ph 230v + E.

**Natural gas flow G20/20 :**

**Propane gas flow G31/37 :**

### OPTIONS

### CODE

AISI 316 L tank - for saline and/or acid foods	V01433
Thermostatic regulation - ranging from 1 to 8	Included
Automatic constant water level - 1~230V+E /0,022 kW	Included
Counter balanced lid - in all position	Included
S/S rear panel fitted in factory - L : 415/840 x H : 645 mm	V01182
Mixer water tap CW/HW Ø 15x21 - swivel spout : 360°	V00561
Mixer water tap CW/HW Ø 15x21 - swivel spout : 180°	V01651
Hole cut to suit client's tap - tap supplied and fitted by client	V01292

### ACCESSORIES

### CODE

S/S clip on plinth panels - 170 mm for standard legs	V01187



