



**HALF MODULE UNIT - 2 SPLIT BURNERS**

**OPEN BASE - 1 FLOOR**

**Pro 900**

**Summary**

**Energy :**

**GAS**

**Code :**

**V03612**

**Designation :**

**1/2B-G2FN**

**Dimensions (W x D x H) :**

**425 x 900 x 900 mm**

**Power : 16,5 kW (gas)**

**Voltage/Electric p. :**

**Weight :**

## DEVICE DESCRIPTION

### General description

**Chassis :**

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity electric welds and lower rear release for passage of cables and supply tubes.

**Top :**

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.

**Base :**

Feet, height 200 mm, in AISI 304 stainless steel tube, diameter 60 mm with adjustable bases (0 / + 30).



**Above :**

- . 2 open burners under cast iron grids of: 420 x 300 mm.
- . Crown type "I.SYSTEM" burners, power: 10 kW at the front - 6.5 kW at the rear, with pilot lights and thermocouple safety.
- . Slack adjustment "stop - ignition - full fire - idle" valves.
- . Enamelled steel removable bowl.
- . 1 grid reducer in stainless steel wire.
- . Cleanliness drawer in 18-10 stainless steel.
- . Grids spaced 100 mm apart.

**Below :**

- . Open base with removable 18-10 stainless steel floor.














**Natural gas flow G20/20 :**

**Propane gas flow G31/37 :**

OPTIONS	CODE
Elec hot cupboard 4xGN2/1 in base - 1~230V+E / 1,50 kW - therm. 0-30/110°C	V00825
Hinged doors - for open base	V01980
Electric spark ignition - 1-230V+E/0,002 kW	V01013
"Double-crown" burner 8 kW - in place of 1 standard burner	V02459
S/S rear panel fitted in factory - W : 415/490 x H : 645 mm	V01181

ACCESSORIES	CODE
S/S clip on plinth panels - H : 170 mm for standard legs	V01186



 <p>Connection gas Gas connection Gasanschl. / Gas Conexi.ó gas</p>	 <p>Connection electric Electric connection Elektrische Verbindung Conexi.ó el.éctrica</p>	 <p>Options Optionen Aussatze Opciones</p>	 <p>Connection water/cold Cold water connection Kaltwasseranschluss Conexi.ó agua fría</p>	 <p>Connection double Hot water connection Warmwasseranschluss Conexi.ó de agua caliente</p>	 <p>Connection standard Shank 11...75 Standard outer connection Shank 75 Standard (optional) outer connection Shank 75 Clase 75 (opcional) estándar Clase 75</p>	 <p>Protection electric tubes  sempre outside  always outside  always</p>
 						
  						
 <p>Ø 15x21 (1/2") 1~230V + PE Ø 1.50mm<sup>2</sup> Opt all elec)</p> <p>V03612 PRO600-1/2B-CUEN-ESPACE-100</p>						



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)



YouTube

