



**HALF MODULE UNITS** - Steel griddle

**BRIDGE UNIT**

**Pro 800**

**Summary**

**Energy:**

**GAS**

**Code :**

**V03679GB**

**Designation :**

**R-G1GRIL-AL**

**Dimensions (L x P x H) :**

**425 x 800 x 320/380mm**

**Power : 11kW (gas)**

**voltage/ electrical power :**

**1~230V+T / 0,01 kW. Weight : 95kg**

## APPLIANCE DESCRIPTION

### General description

**- Frame**

One-piece seam-welded AISI 304 stainless steel chassis, 1.5 to 3 mm thick.

**- Top:**

AISI 304 stainless steel top frame, 2 mm thick, with a 55 mm high edge having a 18 mm radius and return to underside.

**- Legs:**

No legs - To be placed on supporting structure.

**- Top :**

. 1 inclined steel smooth griddle 380x570mm, 20mm thick, with integrated splashguard. Removable grease collector in front of the griddle.

. 1 multi-ramp enameled burner rated 11kW, controlled from 100 to 350°C by a thermostatic gas valve with pilot light and flame failure safety cut-out thermocouple. Option : 100% or 50% ribbed griddle.

.

.

**- Base :**

. Bridge unit

Photo non contractuelle



**Natural Gas Flow G20/20 :**

**Propane Gas Flow G31/37 :**

### OPTIONS

### CODE

150mm wide plating shelf

V00805

100% ribbed griddle

V03705

















50% ribbed griddle

V03707

### ACCESSORIES

### CODE



 <p>Comexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Comexion electrica Electric connection Elektrische Verbindung Conexión electrica</p>	 <p>Options Optionen Aufbaue Opciones</p>	 <p>Comexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Comexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Comexion eau adoucie Softened water connection Softened water connection Wasserzulauf (gefiltertes wasser ≤ 3 bars-7°F) Comexión agua ≤ 3 bars-40.7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserablauf desagüe</p>
				     <p>Ø15/21 (1/2") 3~400V+N+T - 1.5mm<sup>2</sup>-si opt. allu.elec</p>	<p>V03679 PRO800-R-G1-GRIL-AL</p>	



LES AUTHENTIQUES DE LA CUISSON

**CHARVET**

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

[www.charvet.fr](http://www.charvet.fr)

