

## 2 OPEN BURNERS + 1 SOLID TOP ON GN2/1 GAS OVEN

## GAS OVEN

### GENERAL DESCRIPTION

- Top :  
AISI 304 stainless steel top 2 mm thick with a 55 mm high edge having 18 mm radius and return to under

- Chassis :  
one-piece seam welded stainless steel chassis 2 mm thick duct at the back

- Legs :  
. 200 mm high stainless steel legs with adjustable PVC feet (0/+30mm) - diam. : 60mm

- General :  
AISI 304 side and front panels 1.2 mm thick  
Enamel control panel  
Chrome coated aluminium knob

Natural gas G20/20 :	2.86 m3/h
----------------------	-----------

Propane gas G31/37 :	2.10 kg/h
----------------------	-----------

REFERENCE : 80-G3FN/PL



### APPLIANCE DESCRIPTION

Dimensions (mm) : W 800 x D 700 x H 900

- Top :  
2 "Crown" open burners 2x6.5 kW with 330x520 nickel coated pan support  
. Removable spillage tray  
1 built-in solid top measuring W:330 x D:520 "Crown" burners rated 5 kW  
. Refractory cement heat retention tray  
Flame failure safety cut-out thermocouple - pilot ignition - recessed low and high heat controls for each burner  
Lower stainless steel spillage tray

- Base :  
Static gas-fired oven GN2/1 measuring W:650 x D:530 x H:290 mm.  
Stainless steel cassette with 30 mm rock wool insulation.  
3 position enameled steel removable shelf supports with a 70 mm-space between them.  
Enameled steel "multi-ramp" burner rated 9 kW with flame failure safety cut out thermocouple and pilot ignition.  
Thermostatic control range from 50 to 300 degrees Centigrade.  
6 mm thick mild steel base plate.  
AISI 304 stainless steel door with rock wool insulation  
Enamel handle on anodised aluminium supports  
One GN2/1 (530x650 mm) nickel coated oven shelf with anti tilt.













CODE	DIMENSIONS	VOLTAGE	POWER	WEIGHT
------	------------	---------	-------	--------

V07010	800 X 700 X 900 mm	1-230V+E	GAS 27 kW	-
--------	--------------------	----------	-----------	---

OPTIONS	CODE
Electric ignition (1-230V+E)	V07067
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
S/S clip on plinth panels	V07084
Nickel coated wire shelf with anti tilt supports	04051A
Blue-stained backing grid	F00158



 <p>Connexion gaz Gas connection Gasschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufanlage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-L...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-abr. 7°GH) Conexión agua blanda ≤ 3 bars-L...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf desagüe</p>
						<p>  Ø 15x21 (1/2")   1 ~230 V + PE Ø 1.50mm<sup>2</sup>       </p>
<p><b>V07010</b> PRO700-80 G3-FN-PL / FG + OPT-ALL-ELEC</p>						

Charvet se réserve le droit de modifier les caractéristiques techniques de ses matériels sans préavis.

