

2 CHROME GRIDDLE

BRIDGE UNIT

GENERAL DESCRIPTION

- Top :
AISI 304 stainless steel top 2 mm thick with a 55 mm high edge having 18 mm radius and return to under
- Chassis :
one-piece seam welded stainless steel chassis 2 mm thick duct at the back
- General :
AISI 304 side and front panels 1.2 mm thick
Enamel control panel
Chrome coated aluminium knob



APPLIANCE DESCRIPTION

Dimensions (mm) : W 800 x D 700 x H 280

- Top :
2 inclined chrome coated (50 µm) smooth griddle plate measuring 350x495 mm
Grease collection drawer.
Enameled steel "multi-ramp" burner rated 7 kW each
Flame failure safety cut out thermocouple - pilot ignition
8-position thermostatic control valve
Removable refractory cement bars between ramps
- Bridge unit
- Gas rating : 14kW - Electrical : 1-230 V+E

Natural gas G20/20 :	1.27 m3/h
Propane gas G31/37 :	0.93 kg/h









REFERENCE : 80-R-G2CHRL

CODE	DIMENSIONS	VOLTAGE	POWER	WEIGHT
V07028	800 X 700 X 280 mm	1-230V+E	GAS 14 kW	-

OPTIONS	CODE
Base unit 800 open	V07057
Base unit with 4xGN2/1 storage	V07058
Hinged doors	V07062
Electric hot cupboard in base 4 x GN2/1 (1-230V+E) - 1.13 kW	V07064
Electric ignition (1-230V+E)	V07067
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
Ribbed chrome griddle plate	V07092
Mixed smooth/ribbed griddle plate	V07093
S/S clip on plinth panels	V07084



 <p>Connexion gaz Gas connection Gasschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica</p>	 <p>Options Optionen Aufanlage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie ≤ 3bars-L...7°F Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ bars-abr. 7° GH) Conexión agua blanda ≤ 3 bars-L...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf desagüe</p>
				 <p>Ø 15x21 (1/2") 1~230 V + PE Ø 1.50mm²</p> <p>V07028 PRO700-80 G2-GRILL</p>		

Charvet se réserve le droit de modifier les caractéristiques techniques de ses matériels sans préavis.