



BRIDGE UNITS W.400 MM - 1 CHARCOAL GRIDDLE

BRIDGE UNITS

Pro 700

Summary

Energy:

GAS

Code :

V07036

Designation :

40-R-G1GRILPIER

Dimensions (L x P x H) :

400 x 700 x 280 mm

Power : 8 kW (gas)

Voltage/Electric p. : 1-230 V+E

Weight : 125 kg

Device description

General description

Chassis :

Stainless steel sheet frame thickness 20/10.

Top :

20/10 stainless steel top AISI 304 in-line polishing with flanged edge 55 mm.

Feet :

Feet height 200 mm in tube AISI304 stainless steel, diameter 60 mm with adjustable PVC base (0 / +30).

General :

10/10 stainless steel coating AISI 304.



Above :

- . AISI 304 perforated stainless steel grid in 10x10 square tubes, Λ marking at 3 cooking levels, with Bakelite handles.
- . Surface area : 300 x 450 mm.
- . AISI304 stainless steel heating zone with panache.
- . Stone support grid in AISI 304 stainless steel.
- . Multi-ramp burner in anti-corrosion treated steel, P : 8 kW with safety thermocouple (possibility of electric ignition in option).
- . S20 "stop / full fire / slow down" valve.
- . AISI304 stainless steel cleanliness drawer on the front to collect the juices.
- . New refractory bricks :
 - Protects the burner (flames below).
 - Avoids direct grease / burner contact.
 - Optimizes the yield by "direct radiation on food".
- Basement : to be placed or suspended.

Natural gas flow G20/20 :

0,85

Propane gas flow G31/37 :

0,62

OPTIONS

CODE













Open cupboard 400 - for all 400 mm bridge units	V07053
Storage cupboard GN1/1 - for all 400 mm bridge units	V07054
Base unit with drawers - for all 400 mm bridge units	V07074
Hinged door - For open base closure	V07061
Elect. hot cupboard 4xGN1/1in base - 1~230V+E / 0.75 kW - therm. 0-30/110°C	V07063
Electric spark ignition - 1~230V+E /0,002 kW	V07066

ACCESSORIES

CODE

S/S plinth clip on to legs - H : 170 mm for standard legs	V07082



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Optionen Aulage Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Softened water connection Wasserzulauf (gef. filtertes wasser ≤ 3bars-7°F) Conexión agua ≤ 3 bars-4.7°F</p>	 <p>Ecoulement eaux usées sewage outflow wasserlauf desagüe</p>	
    		<p>Ø 15x21 (1/2") 1-230V + PE Ø1.50mm²</p>		<p>V07036-V07053 PRO700-40 GI-GRILLPIER</p>			

Technical characteristics are indicative only and can be modified from Charvet Co. without notice.



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

