

BRATT PAN

GENERAL DESCRIPTION

- Top :

AISI 304 stainless steel top 2 mm thick with a 55 mm high edge having 18 mm radius and return under

- Chassis :

one-piece seam welded stainless steel chassis 2 mm thick duct at the back

- Legs :

. 200 mm high stainless steel legs with adjustable PVC feet (0/+30mm) - diam. : 60mm

- General :

AISI 304 side panels 1.2 mm thick Enamel front panel

Natural gas G20/20 :	1.59 m3/h
----------------------	-----------

Propane gas G31/37 :	1.17 kg/h
----------------------	-----------

REFERENCE : **80-G1SBE**



APPLIANCE DESCRIPTION

Dimensions (mm) : W 800 x D 700 x H 900

- Features :

- . 30 dm² (60l) Stainless steel tank measuring W : 555 x D : 525 x H : 250 (mm internal) with a 10 mm thick base and built in spout.
- . Electric tilting by electromechanical acuator
- . Stainless steel lid tubular handle, stainless steel sprin hinges.

- . Enamelled steel 'Multi-ramps' burner with flame failure safety cut-out thermocouple;
- . Electric sparking ignition.

- Gas rating : 15 kW













- Electrical rating : 0,02 kW / 1~230V+E

CODE	DIMENSIONS	VOLTAGE	POWER	WEIGHT
V07103	800 X 700 X 900 mm	1-230 V+E	GAS 15 kW	

OPTIONS	CODE
10 mm thick bimetal bottom	V07130
Pan tilt safety cut-out	V07131
Removable stainless steel strainer	V07133
Stainless steel plinth to clamp on legs	V07084

ACCESSORIES	CODE
Mixer water tap (HW/CW) 20x27 360°	V00561
Mixer water tap (HW/CW) 20x27 180°	V01651
Hole cut tu suit client's tap	V01292



 <p>Connexion gaz Gas connection Gasanschluss Conexión gas</p>	 <p>Connexion électrique Electric connection Elektrische Verbindung Conexión eléctrica</p>	 <p>Options Options Aufträge Opciones</p>	 <p>Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría</p>	 <p>Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente</p>	 <p>Connexion eau adoucie Softened water connection Wasserzulauf (gefiltertes wasser ≤ bars-ab: 7°GH) Conexión agua blanda ≤ 3 bars-l.h...7°F</p>	 <p>Écoulement eaux usées sewage outflow wasserablauf desagüe</p>
						<p>  Ø 15x21 (1/2")  1~230V + PE Ø 1.5 mm²  Ø 15x21 (1/2")  Ø 15x21 (1/2")  </p> <p>V07103 G SBE 30dm² PRO 700</p>

Charvet se réserve le droit de modifier les caractéristiques techniques de ses matériels sans préavis.

